

CRH1 HOIST UP TO MAX. 1.100KG

This universal clean room hoist has an ultra-compact design with a hoisting capacity of 80 – 1.100 kg. Configurations include fixed and remote control. A competitive price positioning makes it a broadly applicable hoist. The hoist with a powder coating body and stainless steel components guarantees total cleanliness and non outgassing.

HIGHLIGHTS

- WLL 80 - 1.100kg
- 1 Belt-hoist
- Single / double fall hoist
- Wide range of configurations
- Fixed and remote controlled
- CRC dyneema belt
- Height of hoist device 550 mm
- UL listed
- ISO 5 tested at Fraunhofer



About us

As a market leader, we have acquired considerable expertise and established an excellent reputation in the field of cleanroom hoisting design. Each item of hoisting equipment is unique and can be delivered with a diversity of specific options. We offer a range of basic products tailored to your needs. We have single and multiple cranes with single and multiple hoisting units. Our cranes can move in the X,Y and Z motion. All of our cranes are made of class-A materials, are non-contaminating, low-out gassing, accurate and quiet. We incorporate internationally known quality labels. In purchasing our products, you will improve your handling efficiency while making the workplace a more productive and safer environment. Quality equipment combined with a service contract, guarantees 24/7 support for your equipment and reliability.

		CRH1-100	CRH1-200	CRH1-400	CRH1-600	CRH1-800	CRH1-1100
Max. WLL	kg	100	200	400	600	800	1100
Hoisting height	m	4	4	4	4	4	4
Speed	m/min	4.2	4.2	4.2	4.2	4.5	3.9
Motor power	kW	0.18	0.37	0.75	1.1	1.6	1.8
Number of falls		1	1	1	2	2	2
Overload devices					optional	optional	optional
FEM class 1BM		x	x	x	x	x	x
RAL 9010 (color)		x	x	x	x	x	x
Fixed configuration		x	x	x	x	x	x
End switch		x	x	x	x	x	x

Options

UL listed components	x	x	x	x	x	x	x
Frequency controlled	x	x	x	x	x	x	x
Push configuration	x	x	x	x	x	x	x
Speed range	1- 4.2	1- 4.2	1- 4.2	1- 4.2	1- 4.5	1- 3.9	
60Hz configuration	x	x	x	x	x	x	x
Different main power	x	x	x	x	x	x	x

Basic version equipped with relays and main power 400V 50Hz.

CONTACT INFORMATION

MARKETECH
Head Office: 6F., No. 3-2, Yuancyu St.,
Nangang District
Taipei City 115, Taiwan
Tel: 886-2-26558899
www.marketech-crc.com



stainless steel hook

WWW.MARKETECH-CRC.COM